

WROT PRESSURE SOLDER-JOINT FITTINGS — To ANSI B16.22

CAST PRESSURE SOLDER-JOINT FITTINGS — To ANSI B16.18

CAST BRONZE FLARED TUBE FITTINGS — To ANSI B18.26

STREAMLINE COPPER TUBE — TYPES K, L & M — To ANSI H23.1, ASTM B88 and WWT-799 REFRIGERATION

FLARE-TYPE FITTINGS - To ANSI B70.1 and SAE J513

STREAMLINE COPPER REFRIGERATION SERVICE TUBE - To ANSI H23.5, ASTM B280, and WWT-775

STREAMLINE NITROGENIZED ACR HARD DRAWN COPPER TUBE - To ANSI H23.1 Type L, and ASTM B88

Type L, in accordance with ASTM 8280

OXYGEN SERVICE TUBE — To ANSI H23. 1 Types K and L and ASTM B88, Types K and L — hard drawn lengths only - — in accordance to CDA cleanliness specifications and NFPA 56F, Seamless Copper Tube cleaned for Oxygen Gas Service

WROT DWV SOLDER-JOINT FITTINGS - To ANSI B16.29

CAST DWV SOLDER-JOINT FITTINGS - To ANSI B16.23

STREAMLINE COPPER TUBE — TYPE DWV — To ANSI H23.6 and ASTM B306

COPPER PIPE — To ASTM B42

RED BRASS PIPE – To ASTM B43



Product Certification

Elkhart Products Corporation manufactures and/or supplies products which meet the following specifications:

MSS	SP104	Wrought Copper LW Solder Joint Pressure Fittings
ANSI	B16.29-1990	Wrought Copper and Wrought Copper Alloy Solder Joint Drainage Fittings - DWV
ANSI	B16.18-1 984	Cast Copper Alloy Solder Joint Pressure Fittings
ANSI	B16.15-1978	Cast Bronze Threaded Fittings
ANSI	B16.26-1983	Cast Copper Alloy Fittings for Flared Copper Tube
ANSI	B16.23-1984	Cast Copper Alloy Solder Joint Drainage Fittings - DWV
ANSI	B16.24-1 979	Bronze Pipe Ranges and Flanged Fittings

EPC's wrot copper solder joint fittings also are manufactured to comply with the material, performance and installation/joining dimensions of ANSI B16.22. The materials used to manufacture these fittings are also in

compliance with the following specifications;

Tubular Wrought Copper: - ASTM B75 Alloy C12200. Standard Specification for Seamless Copper Tube. or

Products Made From Sheet;

ASTM B152 Alloy C11000, Standard Specification for Copper Sheet Strip, Plate and Rolled Bar.

Cast Products:

ASTM B584 Alloy C84400, Standard Specification for Copper Alloy Sand Castings for General Applications. Federal Specification WW-U-516 for Type III, Class A and Class B Copper Alloy Unions.



B-42	This specification covers seamless copper pipe in all standard pipe sizes, both regular and extra— strong, suitable for use in plumbing, boiler feed lines, and for similar purposes.
B-43	This specification covers seamless red brass (Copper Alloy UNS No. C23000) pipe in all standard pipe sizes, both regular and extra—strong, suitable for use in plumbing, boiler feed lines, and for similar purposes.
B-68	This specification covers annealed seamless copper tube suitable for use in refrigerators, oil lines, gasoline lines, etc, where tube absolutely free from scale end dirt is required.
B-75	This specification covers seamless copper, round and rectangular including square tube suitable for general engineering purposes.
B-88	This specification covers seamless copper water tube suitable for general plumbing, and similar applications for the conveyance of fluids, and commonly used with solder, flared, or compression type fittings.
B-111	This specification covers seamless tube and ferrule stock of copper and various copper alloys up to 2 .in (50.8mm), inc., in diameter, for Use in surface condensers, evaporators, and heat exchangers.
B-135	This specification covers seamless round and rectangular including square copper alloy tube in straight lengths
B-251	This specification covers a group of general requirements common to several wrought product specifications. Unless otherwise specified in the purchase order, or in an individual specification, these general requirements shall apply to copper and copper-alloy tube supplied under specifications B 68, B 75, B135, and B466
B-280	This specification covers seamless copper tube for air conditioning and refrigeration service and intended for use in the field for connection, repairs, and alterations.
B-302	This specification covers threadless, seamless, deoxidized copper pipe (TP) in straight lengths, for piping systems that are assembled with brazed-joint pipe fittings.
B-306	This specification covers seamless copper drainage tube (DWV) intended for use with soldered fittings for sanitary drainage, such as soil, waste, and vent piping.



Product	Temper	Lengths	Color Code	Uses	Specifications
Copper Water Tube	Hard	10 ft straight	Green	Underground services*;	Federal-WW-T-799
Туре К		20 ft. straight		general plumbing and	ASTM- B.88
(heavy wall)				heating purposes; gas,	Underwriters' Approved
		20ft. straight		steam and oil lines; severe	1⁄4" thru 2"
	Soft	40 ft. coils(2")		service conditions.	
		60 ft. coils(1/4" thru 1 1/2")			
		100 ft. coils(1/4" thru 1 1/4")		*soft recommended	
Copper Water Tube,	Hard	10 ft straight	Blue	General plumbing and	Federal- WW-T-799
Type L		20 ft. straight		heating purposes. Interior	ASTM – B-88
Type ACR(hard only)				gas, steam and oil lines:	U.L. Approved Fire
(medium wall)		20ft. straight		panel heating. Type ACR	Service Systems 1/2" -8"
		30ft. coils(1/4" thru 1 1/2")		for air conditioning and	incl.
	Soft	40 ft. coils(2")		refrigeration uses.	
		60 ft. coils(1/4" thru 1 1/2")			
		100 ft. coils(1/4" thru 1 1/4")			
Copper Water Tube	Hard	10 ft. straight	Red	General plumbing and	Federal- WW-T-799
Туре М		20 ft. straight		heating purposes; drainage	ASTM B-88
(light wall)				waste, vent and other light	
				pressure uses.	
Copper Drainage Tube	Hard	10 ft. straight	Yellow	Drainage, waste, vents,	ASTM B-306
		20 ft. straight		soil and other non-	
				pressure applications	
				(above ground use only).	
Copper Pipe	Hard	12 ft. straight	Black	General plumbing and	Navy – 44P2
(regular or extra heavy)		20 ft. straight		heating purposes; gas,	Federal – WW-P-377
				steam and oil lines: severe	ASTM- B-42
				service conditions	
				including high pressure	
				industrial applications	
Copper Threadless	Hard	20 ft. straight	Gray	General plumbing and	ASTM – B-302
Pipe				heating purposes	Federal- WW-T-775
Copper Refrigeration	Soft	50 ft. coils	Crimson	Manufacture, installation	ASTM B-280
Tube		100 ft. coils		and maintenance of	Federal – WW-T-775
				refrigeration equipment	
Special Dimensional	As	As Specified		Special industrial	ASTM B-68
Tube	Specified			applications. Composition	ASTM B-75
				and dimensions to fit	
				individual requirement.	