

FIRE PROTECTION PRODUCTS

PIPE

Light Wall Pipe
Carbon Steel (CW / ERW)
Carbon Steel (Seamless)
Copper (K, L, M, ACR, Ref)
Brass
Grooved Pipe
CPVC (Flameguard)

FITTINGS

Victaulic Grooved System

- Firelock Fittings
- Firelock Couplings
- Firelock IGS Ftgs

Spears CPVC Fittings

- Torquesafe
- Flameguard

Cast Iron Fittings
Malleable Fittings
Pro Press Fittings
O-Lets
Stainless Steel Fittings
Nipples
Megapress

DEVICE ACCESSORIES

Air Maintenance Trim

- Regulated
- w/ Pressure Switch

Accelerator
Actuator
Drain Connection Kit
Dry Valve Trim Kit

UL/FM VALVES

Ball Valves

- w/ Tamper Switch

Bronze Globes
Bronze Checks
3-way Valve
Grooved Check
Grooved Butterfly Valve

- w/ Tamper Switch
- Normally Closed

Ball Drip
Angle Valve
Hose Valves
OS & Y / RW Gate
Test & Drain
Testmasters
Bermad PRV's

SPRINKLER HEADS

Commercial
Residential
Concealed
Dry
Extended Coverage
ESFR
Large Orifice
Vic Flex
Globe

STRAINERS

Cast Iron
Cast Steel
Bronze
Epoxy Coated

BACKFLOW PREVENTERS

Reduced Pressure
Double Check
Double Check Detector
Repair Kits / Air Gaps

DEVICES

Victaulic NXT Dry Valve

- Quick Riser
- Pre-Trimmed

Victaulic Alarm Valve

- Pre-Trimmed

Victaulic Pre-Action Valve
Victaulic Deluge Valve
Victaulic Wet Alarm Valve
Victaulic Fire Pac
Victaulic Riser Manifold
Victaulic Riser Check

- With Trim

Victaulic Compressors

SPECIALTIES

Bolts/Nuts/Gaskets
Pipe Hangers
All Threaded Rod
Glycerin
Glycol
Potter Alarm Switches
Head Boxes
Head Cages
Storz Connections
Backboxes
Pipe Preparation Tools
Pipe Preparation Machines
Head Wrenches

SALES & WAREHOUSE LOCATIONS

MA-CANTON

6 WHITMAN RD.
CANTON, MA 02021
(781) 828-8500
FAX (781) 828-1321

MA-SOMERVILLE

12 FIRST AVENUE
SOMERVILLE, MA 02143
(617) 629-0500
FAX (617) 629-2004

RHODE ISLAND

80 COYLE AVENUE
PAWTUCKET, RI 02860
(401) 725-1700
FAX (401) 724-7250

CT-WINDSOR

134 ADDISON RD.
WINDSOR, CT 06095
(860) 243-8500
FAX (860) 286-8386

CT-NEW HAVEN

204-216 CHAPEL STREET
NEW HAVEN, CT 06513
(203) 776-8500
FAX (203) 562-2740

NEW HAMPSHIRE

777 EAST INDUSTRIAL PARK DR.
MANCHESTER, NH 03109
(603) 645-8500
FAX (603) 647-5587

VERMONT

25 COMMERCIAL AVENUE
S. BURLINGTON, VT 05403
(802) 660-8500
FAX (802) 660-9500

NEW YORK

4 ENTERPRISE DRIVE
ALBANY, NY 12204
(518) 463-8500
FAX (518) 463-1125

Style 912 FireLock Low-Profile Sprinkler Tee
Style 922 FireLock Outlet-T
Style 923 Vic-Let Strapless Outlet
Style 924 Vic-O-Well Strapless Thermometer Outlet

| | Style 912 | | Style 922 | | Styles 923/924 | |
|-----------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| | Minimum Hole Size inches/mm | Maximum Hole Size inches/mm | Minimum Hole Size inches/mm | Maximum Hole Size inches/mm | Minimum Hole Size inches/mm | Maximum Hole Size inches/mm |
| All Sizes | 15/16 24 | 1 25 | 1 3/16 30 | 1 1/4 32 | 1 1/2 38 | 1 9/16 40 |

Styles 920 and 920N Mechanical-T Bolted Branch Outlets

| NOTICE |
|--|
| <ul style="list-style-type: none"> For proper installation, some new sizes of Style 920N products require a different hole size than the Style 920 or Style 921 it replaces. Make sure the proper size hole is prepared for the size and style being installed (refer to the table below for requirements). |

| Size | Hole Dimensions inches/mm | |
|-----------------------------|-------------------------------------|----------------------------|
| | Minimum Hole Diameter/Hole Saw Size | Maximum Allowable Diameter |
| All 1/2-inch/21.3 Outlets | 1 1/2 38 | 1 5/8 41 |
| All 3/4-inch/26.9 Outlets | 1 1/2 38 | 1 5/8 41 |
| All 1-inch/33.7 Outlets | 1 1/2 38 | 1 5/8 41 |
| All 1 1/4-inch/42.4 Outlets | 1 3/4 44 | 1 7/8 48 |
| All 1 1/2-inch/48.3 Outlets | 2† 51 | 2 1/8 54 |
| All 2-inch/60.3 Outlets | 2 1/2‡ 64 | 2 5/8 67 |
| All 2 1/2-inch/73.0 Outlets | 2 3/4 70 | 2 7/8 73 |
| All 76.1-mm Outlets | 2 3/4 70 | 2 7/8 73 |
| All 3-inch/88.9 Outlets | 3 1/2 89 | 3 5/8 92 |
| All 4-inch/114.3 Outlets | 4 1/2 114 | 4 5/8 118 |
| All 108.0-mm Outlets | 4 1/2 114 | 4 5/8 118 |

† 2 x 1 1/2-inch/60.3 x 48.3-mm Style 920N products require a 1 3/4 -inch/44-mm hole.

‡ 8 x 2-inch/219.1 x 60.3-mm Style 920 products require a 2 3/4-inch/70-mm size hole.

NOTE: Style 920 and Style 920N housings CANNOT be mated to each other to achieve cross connections.